


SPECIFICATIONS

		MCC-4	MCC-6	MCC-8	MCC-10	MCC-12
Weight (Nominal)	<i>Oz.</i>	2.0	4.5	9.1	14.8	28.1
Volts	<i>D.C.</i>	24 to 28	24 to 28	24 to 28	24 to 28	24 to 28
Coil Resistance $\pm 10\%$	<i>Ohms</i>	246.0	193.0	169.0	150.0	144.0
Clutch Torque Minimum @ 24 V.D.C. (Either Coil)	<i>Oz. In.</i>	6.0	26.0	64.0	100.0	256.0
Response Time @ 28 V.D.C. (Ener.) (Either Coil)	<i>MS Nom.</i>	5.0	11.0	13.0	17.0	34.0
Maximum No Load Torque (Drag) Energized	<i>Oz. In.</i>	.05	.25	.40	.60	1.0
Maximum No Load Torque (Drag) De-energized	<i>Oz. In.</i>	.05	.10	.15	.20	1.0
Polar Moment of Inertia - Input Gear Flange (A)	<i>In. Lb. Sec²</i>	0.4×10^{-6}	3.8×10^{-6}	11.5×10^{-6}	20.2×10^{-6}	91.1×10^{-6}
Polar Moment of Inertia - Input Gear Flange (B)	<i>In. Lb. Sec²</i>	0.4×10^{-6}	3.8×10^{-6}	11.5×10^{-6}	20.2×10^{-6}	91.1×10^{-6}
Polar Moment of Inertia - Output Shaft	<i>In. Lb. Sec²</i>	0.5×10^{-6}	3.8×10^{-6}	13.8×10^{-6}	26.4×10^{-6}	84.7×10^{-6}



DIMENSIONAL DATA

	A	B	C	D	E	F	G	H	J	L	M*	N*	O*	P	R	S	T	U	V	W	X
Model	$\pm .010$	$\pm .015$	$\pm .010$	$\pm .020$	$+.003$ $-.000$	$\pm .005$	$\pm .005$	$\pm .005$	$\pm .015$	$\pm .005$	$+.0000$ $-.0005$	$+.0000$ $-.0005$	$+.0000$ $-.0005$	$+.000$ $-.005$	$\pm .005$	2B THD	$\pm .002$	$\pm .005$	REF	REF	REF
MCC-4	.531	1.581	.425	.300	.047	.060	.125	.079	2.589	.578	.0935	.2190	.5000	.594	.344	#0-80	.056	.450	.578	.150	.245
MCC-6	.750	2.271	.511	.300	.060	.100	.170	.120	3.451	.796	.1248	.3750	.7500	.827	.625	#2-56	.061	.740	.880	.229	.368
MCC-8	1.000	2.753	.605	.375	.060	.100	.177	.177	4.211	1.080	.1248	.5000	1.0000	1.090	.750	#2-56	.064	.934	1.074	.224	.431
MCC-10	1.250	2.986	.650	.375	.060	.125	.203	.177	4.496	1.350	.1873	.5000	1.2500	1.370	.750	#2-56	.064	.934	1.168	.221	.387
MCC-12	1.562	3.369	.885	.500	.092	.132	.237	.177	5.197	1.680	.2498	.6250	1.5620	1.740	1.000	#2-56	.090	1.200	1.242	.221	.451

* Concentric within .0015 T.I.R.